



Raising the Bar

Manufactured with high quality glass fiber and polyester resin,

GlassBar is built to be stronger, lighter and rust free!

GlassBar is non-magnetic, making it electrically non-conductive as well as thermally non-conductive. Packaged in 50 piece bundles for easy shipping and handling.



RUST FREE

Does not corrode, extended structure life



LIGHTWEIGHT

Large labor & freight savings




NON-CONDUCTIVE

GlassBar is electrically non-conductive and thermally non-conductive



STRONGER THAN STEEL

GlassBar outperforms traditional black bar in all ASTM testing criteria



INSTALLS LIKE STEEL

Tie it off and chair it up just like steel!

Nominal Diameter Area

- 12 mm (113mm²)
- 1/2 in (.175in²)

Lengths

- Up to 20 ft

Weight

- .1 lb/ft

Ultimate Tensile Strength ASTM 7205

- 113.3 KSI
- 782.5 MPA

Ultimate Tensile Load ASTM 7205

- 19,869 lbs
- 88.5 KN

Tensile Modulus of Elasticity ASTM 7205

- 6000 KSI
- 41.4 GPa

Guaranteed Transverse Shear Capacity ASTM 7617

- 150 MPA

Moisture Content ASTM D570

- <.5%

Bond Strength AG440.3RB3

- 669 PSI
- 1700 lbs
- 4.6 MPA

Fiber Content

- 70% - 80% by weight

LiteForm® GLASSBAR



Raising the Bar

Reduce Labor & Increase Profit with Glassbar.
Call us at **800.551.3313** for your quote!