



Raising the Bar

Manufactured with high quality glass fiber with polyester resin or optional vinyl ester resin. Glassbar is built to be stronger, lighter, and rust free! GlassBar is non-magnetic, making it electrically non-conductive as well as thermally non-conductive. Packaged in 50 piece bundles for easy shipping and handling.



RUST FREE

Does not corrode, extended structure life



LIGHTWEIGHT

Large labor & freight savings




NON-CONDUCTIVE

GlassBar is electrically non-conductive and thermally non-conductive



STRONGER THAN STEEL

GlassBar outperforms traditional black bar in all ASTM testing criteria



INSTALLS LIKE STEEL

Tie it off and chair it up just like steel!

Nominal Diameter Area

- 11mm
- 7/16 in (.150in²)

Lengths

- Up to 20 ft

Weight

- .1 lb/ft

Ultimate Tensile Strength ASTM 7205

- 126 ksi
- 869 MPa

Ultimate Tensile Load ASTM 7205

- 18,947 lbs
- 84.3 kN

Tensile Modulus of Elasticity ASTM 7205

- 6,450 ksi
- 44.5 GPa

Guaranteed Transverse Shear Capacity ASTM 7617

- 21.1 ksi
- 145.5 MPa

Moisture Content ASTM D570

- <.5%

Fiber Content

- >80% by weight

LiteForm[®] GLASSBAR



Raising the Bar

Reduce Labor & Increase Profit with Glassbar.
Call us at **800.551.3313** for your quote!